

DefendAL®



Heavy Duty Pre-Charged Antifreeze/Coolant

DefendAL® Heavy Duty Pre-Charged Antifreeze/Coolant is a premium quality conventional technology, virgin ethylene glycol-based fluid. Specially formulated with additive technology designed to protect heavy duty engines, this product provides protection without an initial charge of SCAs. Meets conventional coolant requirements of most industry-leading OEMs.

- No initial charge of SCAs required - use DefendAL SCA to maintain fluid at recommended maintenance intervals
- Phosphate-free with low silicate
- Meets or exceeds: ASTM D3306, ASTM D6210, TMC RP329
- Service life of 300,000 miles | 6,000 hours of offroad use*

*Fluid must be maintained using DefendAL SCA approximately every 30,000 miles. Consult your vehicle's owner's manual for recommendations.

DefendAL® Heavy Duty Pre-Charged Antifreeze/Coolant is your cooling system's best defense.

- Contains nitrites for superior wet sleeve liner cavitation protection
- Provides maximum freeze and boil-over protection
- Corrosion protection for steel, solder, copper, iron, brass and aluminum
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Compatible with all major American brands of conventional coolants
- Ideal for older Cummins, Detroit Diesel, Navistar, John Deere, or mixed fleets - see list of specifications for additional applications

Available in:

Concentrate

Bulk #10225
Totes #10223
Drums #10230
Cases #11161

50/50 Premix

Bulk #10240
Totes #10235
Drums #10245
Cases #11162

KOSTUSA
a Recochem Company

DefendAL® Heavy Duty Pre-Charged Antifreeze/Coolant

Technical Information	Concentrate	50/50
Fluid Color	Fuchsia	Fuchsia
Density @ 68°F, lb/gal	9.3	8.9
pH (50v% solution)	10.5	10.5
Maintenance Interval, miles (hours)	30,000 (600)	30,000 (600)
Coolant Lifetime, miles (hours)	300,000 (6,000)	300,000 (6,000)

FREEZE/BOIL PROTECTION CHART <small>*Using a 15psi pressure cap</small>	% Cooling System Capacity	PROTECTION FROM	
		Freezing Down To	Boiling Up To†
	40	-13° F	+260° F
	50	-34° F	+265° F
	60	-62° F	+270° F

Shipping Information	Cases	Steel Drums	Totes
Package Quantity	3x1 Gallons	55 Gallons	275 Gallons
Package Dimensions	12.75" x 7.8" x 12"	23.5"D x 34.5"H	40" x 48" x 53"
Gross Container Weight - Concentrate	≈30 Pounds	≈550 Pounds	≈2703 Pounds
Gross Container Weight - 50/50	≈29 Pounds	≈528 Pounds	≈2594 Pounds
Gross Weight on Pallet - Concentrate	≈2197 Pounds	≈2262 Pounds	≈2703 Pounds
Gross Weight on Pallet - 50/50	≈2110 Pounds	≈2174 Pounds	≈2594 Pounds
Quantity Per Pallet	72	4	1
Pallet Dimensions	40" x 48" x 54.5"	48" x 48" x 39.4"	40" x 48" x 53"
Product Part Number - Concentrate	11161	10230	10223
Product Part Number - 50/50	11162	10245	10235
UPC Code - Concentrate	652138268526	652138100659	652138100666
UPC Code - 50/50	652138268533	652138100673	652138100680
UPC Case Code - Concentrate	652138101182	N/A	N/A
UPC Case Code - 50/50	652138101199	N/A	N/A
Weight Per Gallon - Concentrate	≈9.3 Pounds	≈9.3 Pounds	≈9.3 Pounds
Weight Per Gallon - 50/50	≈9 Pounds	≈9 Pounds	≈9 Pounds

WARNING: REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.

DefendAL® Heavy Duty Pre-Charged

Recommended for use in:

ASTM D3306
ASTM D6210
BS 6580:2010
Buhler Versatile 86050054
CAT DEAC
CAT EC-1

CID-A-52624A
CNH MAT 3620 EG3, EG4
Cummins CES 14439
Cummins CES 14603
Daimler DBL 7700
Detroit Diesel 7SE298

Deutz H 0685-6: Class DQC CA-14
Ford ESE-M97B18-C
JCB STD00088
John Deere JDM H24A1, A2
MAN 324 Type N
MWM Deutz TR0199-99-2091

Navistar CEMS B-1 Type II
Navistar MPAPS MPAPS B-1 Type II
Perkins (CAT) SEBU7833-03
TMC RP 329
Volvo Coolant Requirements: Volvo Trucks

Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures.



KOST USA, Inc. recommends to always properly dispose of spent coolant. Contact your state or local municipality for instructions on proper disposal to protect our environment. If a coolant spill occurs, call local authorities and ask for proper instruction on how to clean up the spill.



KOST® USA is the Largest Family-Founded Manufacturer, Supplier, and Marketer of Antifreeze, Glycols, and Functional Fluids in the United States. Founded in 1985 and Headquartered in Cincinnati, OH. We Proudly Build our Customer's Private Label Brands and our Oil & Gas brands through High-Performance Products and Superior Service. Our business is primarily in the Automotive & Heavy-Duty Aftermarket.

1-800-661-9391 | kostusa.com

