

Winter Proof Water System Antifreeze

SECTION 1. IDENTIFICATION

Product Identifier	Winter Proof Water System Antifreeze
Other Means of Identification	35-364WP, 35-365WP, 35-369WP, 35-365WPTRAY, 85-364AZ
Other Identification	Absolute Zero RV Waterline Antifreeze
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer/Supplier Identifier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1869

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 3; Eye irritation - Category 2B; Carcinogenicity - Category 2

Label Elements



Signal Word:
Warning

Hazard Statement(s):

H226	Flammable liquid and vapour.
H320	Causes eye irritation.
H351	Suspected of causing cancer if swallowed.

Precautionary Statement(s):

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P241	Use explosion-proof equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash hands and skin thoroughly after handling.

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1
Date of Preparation: June 29, 2017
Date of Last Revision: April 12, 2019

SDS No.: 1869

Page 01 of 09

P280 Wear protective gloves, eye protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to extinguish.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Note:

3.10

% of the mixture consists of ingredient(s) of unknown acute toxicity inhalation.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Ethanol	64-17-5	10-30		
1,2-Propylene glycol	57-55-6	1-5		

Notes

Use of Generic SDS:

If the concentration or actual concentration range of an ingredient of a particular hazardous product in the series is different from the concentration or actual concentration range disclosed for the rest of the series, either the concentration or the actual concentration range must be indicated beside that ingredient under item 3 (Composition/Information on ingredients) of the SDS. Furthermore, if any other specific information element(s) (such as flash point, numerical measure of toxicity, etc.) for a particular hazardous product in the series differs from that of the other products in the series (without affecting the classification), the information element relevant to that hazardous product must be disclosed on the SDS with an indication to which hazardous product each relates.

Source: Health Canada - Technical Guidance on the Requirements of the Hazardous Products Act and the Hazardous Products Regulations WHMIS 2015 Supplier Requirements - pg 117

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 02 of 09

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Get medical advice or attention if you feel unwell or are concerned. If skin irritation occurs, get medical advice or attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Immediate Medical Attention and Special Treatment

Target Organs

Liver, eyes, nervous system, skin.

Special Instructions

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Medical Conditions Aggravated by Exposure

Dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. See Section 9 (Physical and Chemical Properties) for flash point and explosive limits. See Section 9 (Physical and Chemical Properties) for explosive limits. Causes fire through friction.

In a fire, the following hazardous materials may be generated: very toxic carbon monoxide, carbon dioxide.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 03 of 09

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Ethanol	1000 ppm	1000 ppm	1000 ppm			
1,2-Propylene glycol	Not established	Not established	Not established	Not established	10 mg/m ³	Not established

Appropriate Engineering Controls

General ventilation is usually adequate. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Not required but it is good practice to wear safety glasses or chemical safety goggles.

Skin Protection

Not required, if used as directed.
Nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Available in these colours: Clear, Yellow, Gold, Red, Blue, Green, Amber, Pink, Orange, Purple, White, Brown, Grey, Teal.
Odour	Alcoholic
Odour Threshold	Not available
pH	7.5 - 8.5 (100% solution)
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Initial Boiling Point/Range	Not available
Flash Point	35 °C (95 °F) (closed cup)
Evaporation Rate	Not available

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 04 of 09

Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	19% (Ethanol) (upper); 3.3% (Ethanol) (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	0.96 - 0.98 at 20 °C
Solubility	Soluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	363 °C (685 °F) (Ethanol)
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity

None known.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 12.0 °C (53.6 °F)

Incompatible Materials

Strong oxidizing agents (e.g. perchloric acid), strong acids (e.g. hydrochloric acid), strong bases (e.g. sodium hydroxide).

Not corrosive to metals.

Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Ethanol	21000 mg/m ³ (mouse) (4-hour exposure)	3450 mg/kg (mouse)	> 15800 mg/kg (rabbit)
1,2-Propylene glycol	Not available	14800 mg/kg (rabbit)	20800 mg/kg (rabbit)

LC50: Not applicable.

ATE Oral: 14,557.38 mg/kg

ATE Dermal: 62,502.85 mg/kg

Skin Corrosion/Irritation

Human experience and animal tests show no or very mild irritation.

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1
Date of Preparation: June 29, 2017
Date of Last Revision: April 12, 2019

SDS No.: 1869

Page 05 of 09

Serious Eye Damage/Irritation

Human experience and animal tests show serious eye irritation. (Ethanol)

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May be harmful as a mist nose and throat irritation.

May be harmful as a mist at high concentrations depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

Skin Absorption

Not harmful based on animal tests.

Ingestion

May be harmful based on human experience. Depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. A severe exposure can cause unconsciousness.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause Following skin contact: dermatitis. Symptoms may include dry, red, cracked skin (dermatitis).

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer.

Human experience shows an allergic skin reaction (skin sensitization) in rare cases following exposure at work. (Ethanol)

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Ethanol	Group 1	A3	Not Listed	Not Listed
1,2-Propylene glycol	Not Listed	Not designated	Not Listed	Not Listed

Carcinogenicity classification is based on alcoholic beverage consumption and not relevant to occupational exposures.

Key to Abbreviations

Group 1 = Carcinogenic to humans. A3 = Animal carcinogen.

Reproductive Toxicity

Development of Offspring

May harm the unborn child. Known to cause: embryotoxic (late resorptions) teratogenic(external, soft tissue and skeletal defects) decreased weight. These effects are not considered relevant to occupational exposures.

Sexual Function and Fertility

Studies in people show effects on sexual function and/or fertility. Known to cause: effects in men and women. These effects are not considered relevant to occupational exposures.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Causes mutagenicity in non-reproductive (somatic) cells in tests using live animals. These effects are not considered relevant to occupational exposures.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

Ecotoxicity

Acute Aquatic Toxicity

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 06 of 09

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Ethanol	42 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	2 mg/L (Daphnia magna (water flea); 48-hour; fresh water)		
1,2-Propylene glycol	Not available	10000 mg/L (Daphnia magna (water flea); 48-hour)		

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Ethanol			< 6300 mg/L (Daphnia magna (water flea); fresh water)	
1,2-Propylene glycol	52930 mg/L (Pimephales promelas (fathead minnow); 96 hrs)		Not available	

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

This section is not required by WHMIS 2015. This section is not required by OSHA HCS 2012.

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1987	ALCOHOLS, N.O.S. (Ethanol)	3	III
US DOT	1987	ALCOHOLS, N.O.S. (Ethanol)	3	III

Environmental Hazards Not applicable

Special Precautions Please note: In containers of 450L or less, this product meets the requirements for exemption under TDG regulation special provisions, part 1, section 1.36b: Class 3, Flammable liquids:

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 07 of 09

Alcohol Exemption.

In containers of 450L or less, this product meets the requirements of DOT exemption as per 49 CFR, section 173.150 (e).

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Proof of Dangerous Goods Classification

Date of Classification February 01, 2017
Technical Name ALCOHOLS, N.O.S.
Classification 3 PG III
Classification Method Flashpoint as per Section 9

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Custom Regulatory 1

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

SECTION 16. OTHER INFORMATION

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544

Date of Preparation June 29, 2017

Date of Last Revision April 12, 2019

Revision Indicators The following SDS content was changed on October 05, 2017:
SECTION 14. TRANSPORT INFORMATION; Special Precautions.

The following SDS content was changed on September 10, 2018:
SECTION 1. IDENTIFICATION; Other Means of Identification.

The following SDS content was changed on April 12, 2019:
SECTION 1. IDENTIFICATION; Other Means of Identification; Other Identification.

References CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.

Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Disclaimer Notice to reader: To the best of our knowledge, the information contained herein is accurate.

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1

SDS No.: 1869

Date of Preparation: June 29, 2017

Date of Last Revision: April 12, 2019

Page 08 of 09

However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Winter Proof Water System Antifreeze - Ver. 1
Date of Preparation: June 29, 2017
Date of Last Revision: April 12, 2019

SDS No.: 1869

Page 09 of 09