



## DefendAL HD ELC Coolant Concentrate and RTU

### KOST USA

Version No: 7.18

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 10/18/2023

Print Date: 10/18/2023

S.GHS.USA.EN

#### SECTION 1 Identification

##### Product Identifier

Product name	DefendAL HD ELC Coolant Concentrate and RTU
Chemical Name	Not Applicable
Synonyms	AX 10262
Proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (ethylene glycol)
Chemical formula	Not Applicable
Other means of identification	Not Available

##### Recommended use of the chemical and restrictions on use

Relevant identified uses	For use as antifreeze/coolant in the coolant systems of heavy duty engines
--------------------------	--

##### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	KOST USA
Address	1000 Tennessee Ave, Cincinnati, OH 45229 Ohio United States
Telephone	Not Available
Fax	Not Available
Website	<a href="http://www.KOSTUSA.com">www.KOSTUSA.com</a>
Email	<a href="mailto:sales@kostusa.com">sales@kostusa.com</a>

##### Emergency phone number


Association / Organisation	POISON CONTROL
Emergency telephone numbers	1-800-222-1222
Other emergency telephone numbers	Not Available

#### SECTION 2 Hazard(s) identification

##### Classification of the substance or mixture

Classification	Acute Toxicity (Oral) Category 4, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Repeated Exposure Category 2
----------------	---

##### Label elements

Hazard pictogram(s)	
Signal word	Warning

##### Hazard statement(s)

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure. (Oral, Dermal)

##### Hazard(s) not otherwise classified

Not Applicable

## DefendAL HD ELC Coolant Concentrate /RTU

## Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.

## Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P330	Rinse mouth.

## Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

## SECTION 3 Composition / information on ingredients

## Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
629-25-4	0.1-1	<u>sodium laurate</u>
1310-58-3	0.1-1	<u>potassium hydroxide</u>
107-21-1	>90	<u>ethylene glycol</u>
64665-57-2*	0.1-1	<u>Sodium Tolyltriazole</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## SECTION 4 First-aid measures

## Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>
Ingestion	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

## Most important symptoms and effects, both acute and delayed

See Section 11

## Indication of any immediate medical attention and special treatment needed

- ▶ Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- ▶ Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- ▶ Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Continued...

## DefendAL HD ELC Coolant Concentrate, RTU

## SECTION 5 Fire-fighting measures

## Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

## Special hazards arising from the substrate or mixture

## Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul>
Fire/Explosion Hazard	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> <li>▶ Mists containing combustible materials may be explosive.</li> </ul> <p>Combustion products include:</p> <ul style="list-style-type: none"> <li>, carbon dioxide (CO2)</li> <li>, other pyrolysis products typical of burning organic material.</li> </ul>

## SECTION 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures

See section 8

## Environmental precautions

See section 12

## Methods and material for containment and cleaning up

Minor Spills	<p>Environmental hazard - contain spillage. Slippery when spilt.</p> <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>
Major Spills	<p>Environmental hazard - contain spillage. Slippery when spilt. Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul>
---------------	--

Continued...

## DefendAL HD ELC Coolant Concentrate/RTU

	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> enter confined spaces until atmosphere has been checked.</li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ When handling, <b>DO NOT</b> eat, drink or smoke.</li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> <li>▶ <b>DO NOT</b> allow clothing wet with material to stay in contact with skin</li> </ul>
Other information	<p>Consider storage under inert gas.</p> <ul style="list-style-type: none"> <li>▶ Material is hygroscopic, i.e. absorbs moisture from the air. Keep containers well sealed in storage.</li> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> use aluminium or galvanised containers</li> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul style="list-style-type: none"> <li>▶ Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.</li> </ul> <p>Alcohols</p> <ul style="list-style-type: none"> <li>▶ are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.</li> <li>▶ reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen</li> <li>▶ react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium</li> <li>▶ should not be heated above 49 deg. C. when in contact with aluminium equipment</li> </ul> <p>Ethylene glycol:</p> <ul style="list-style-type: none"> <li>▶ reacts violently with oxidisers and oxidising acids, sulfuric acid, chlorosulfonic acid, chromyl chloride, perchloric acid</li> <li>▶ forms explosive mixtures with sodium perchlorate</li> <li>▶ is incompatible with strong acids, caustics, aliphatic amines, isocyanates, chlorosulfonic acid, oleum, potassium bichromate, phosphorus pentasulfide, sodium chlorite</li> <li>▶ Avoid strong acids, bases.</li> </ul>

## SECTION 8 Exposure controls / personal protection

## Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	potassium hydroxide	Potassium hydroxide	Not Available	Not Available	2 mg/m3	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D

## Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
potassium hydroxide	0.18 mg/m3	2 mg/m3	54 mg/m3
ethylene glycol	30 ppm	150 ppm	900 ppm
Sodium Tolytriazole	1.9 mg/m3	21 mg/m3	130 mg/m3

Ingredient	Original IDLH	Revised IDLH
sodium laurate	Not Available	Not Available
potassium hydroxide	Not Available	Not Available
ethylene glycol	Not Available	Not Available
Sodium Tolytriazole	Not Available	Not Available

## Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
sodium laurate	E	≤ 0.01 mg/m³
Sodium Tolytriazole	E	≤ 0.01 mg/m³

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

## Exposure controls

Continued...

## DefendAL HD ELC Coolant Concentrate/RTU

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <thead> <tr> <th>Type of Contaminant:</th><th>Air Speed:</th></tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td><td>0.25-0.5 m/s (50-100 f/min.)</td></tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s (100-200 f/min.)</td></tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min.)</td></tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td><td>2.5-10 m/s (500-2000 f/min.)</td></tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th><th>Upper end of the range</th></tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr> <tr> <td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr> <tr> <td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
Type of Contaminant:	Air Speed:																				
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)																				
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)																				
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)																				
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)																				
Lower end of the range	Upper end of the range																				
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																				
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity																				
3: Intermittent, low production.	3: High production, heavy use																				
4: Large hood or large air mass in motion	4: Small hood-local control only																				
<b>Individual protection measures, such as personal protective equipment</b>																					
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>																				
<b>Skin protection</b>	See Hand protection below																				
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul>																				

Continued...

## DefendAL HD ELC Coolant Concentrate/RTU

	<p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

DefendAL HD ELC Coolant Concentrate

Material	CPI
NEOPRENE	A
BUTYL	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
TEFLON	C
VITON	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	1.0706
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.4	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available

Continued...

## DefendAL HD ELC Coolant Concentrate /RTU

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>100	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (50%)	7.6-8.5
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

Inhaled	<p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.</p>
Ingestion	<p>The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.</p> <p>If swallowed, the toxic effects of glycols (dihydric alcohols) are similar to those of alcohol, with depression of the central nervous system, nausea, vomiting, and degenerative changes in the liver and kidney.</p> <p>Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma.</p> <p>For ethylene glycol:</p> <p>Symptoms following swallowing ethylene glycol include failure of breathing, central nervous system depression, cardiovascular collapse, lung swelling, acute kidney failure, and even brain damage. Swallowing 100 millilitres has caused death.</p> <p>There are three stages of ethylene glycol poisoning. The severity of each stage depends upon the amount of ethylene glycol swallowed.</p> <p>There is usually minimal damage to the liver. In the first 12 hours, central nervous system depression is seen. A temporary feeling of exhilaration occurs, without the odour of ethanol. There may be gastrointestinal complaints including nausea and vomiting. Acidosis, coma, convulsions and seizures may also occur. Disorders in eye movements may occur, although otherwise eye examination usually remains normal.</p> <p>At 12-24 hours after swallowing, effects on the lung and heart appear. These are characterized by fast heart rate, fast breathing, and mildly high blood pressure. Congestive heart failure and circulatory collapse may occur in severe poisonings. Effects on the kidney are seen 24-72 hours post-ingestion and are characterized by reduced urine output, flank pain, death of kidney tubules, kidney failure, and rarely, failure of the bone marrow. Kidney damage may be permanent.</p> <p>Acid base disturbances (acidosis) in the blood result from the formation of glycolic acid and some lactic acid.</p> <p>Animal testing showed that ethylene glycol, if swallowed during pregnancy, may lead to birth defects.</p> <p>Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p>
Skin Contact	<p>The material may accentuate any pre-existing dermatitis condition</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>
Eye	<p>There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p>
Chronic	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Exposure to ethylene glycol over a period of several weeks may cause throat irritation, mild headache and low backache. These may worsen with increasing concentration of the substance. They may progress to a burning sensation in the throat, a burning cough, and drowsiness.</p>

Continued...

## DefendAL HD ELC Coolant Concentrate /RTU

DefendAL HD ELC Coolant Concentrate	TOXICITY	IRRITATION
	Not Available	Not Available
sodium laurate	TOXICITY	IRRITATION
	Not Available	Skin (rat): 28 mg/24h - SEVERE
potassium hydroxide	TOXICITY	IRRITATION
	Oral (Rat) LD50: 273 mg/kg <sup>[2]</sup>	Eye (rabbit): 1mg/24h rinse-moderate
		Skin (human): 50 mg/24h SEVERE
		Skin (rabbit): 50 mg/24h SEVERE
ethylene glycol	TOXICITY	IRRITATION
	dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg/1h - mild
	Oral (Rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye (rabbit): 12 mg/m3/3D
		Eye (rabbit): 1440mg/6h-moderate
		Eye (rabbit): 500 mg/24h - mild
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 555 mg(open)-mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
Sodium Tolytriazole	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg (24 hr) <sup>[2]</sup>	Eye (rabbit): Corrosive
	Inhalation(Rat) LC50: >17500 mg/m3/3h <sup>[2]</sup>	Skin (rabbit): Corrosive
	Oral (Rat) LD50: 1980 mg/kg (male) <sup>[2]</sup>	Skin: adverse effect observed (corrosive) <sup>[1]</sup>
	Oral (Rat) LD50: 675 mg/kg (female) <sup>[2]</sup>	
	Oral (Rat) LD50: 735 mg/kg (female) <sup>[2]</sup>	
	Oral (Rat) LD50: 920 mg/kg (male) <sup>[2]</sup>	
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

DefendAL HD ELC Coolant Concentrate	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.
DefendAL HD ELC Coolant Concentrate & SODIUM LAURATE & POTASSIUM HYDROXIDE & Sodium Tolytriazole	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
DefendAL HD ELC Coolant Concentrate & ETHYLENE GLYCOL	<p>For ethylene glycol:</p> <p>Ethylene glycol is quickly and extensively absorbed throughout the gastrointestinal tract. Limited information suggests that it is also absorbed through the airways; absorption through skin is apparently slow. Following absorption, it is distributed throughout the body. In humans, it is initially metabolized by alcohol dehydrogenase to form glycoaldehyde, which is rapidly converted to glycolic acid and glyoxal. These breakdown products are oxidized to glyoxylate, which may be further metabolized to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate carbon dioxide, which is one of the major elimination products of ethylene glycol. In addition to exhaled carbon dioxide, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination is rapid and occurs within a few hours.</p> <p>Respiratory effects: Respiratory system involvement occurs 12-24 hours after swallowing sufficient amounts of ethylene glycol. Symptoms include hyperventilation, shallow rapid breathing, and generalized swelling of the lungs with calcium oxalate deposits occasionally appearing in the lungs. Respiratory system involvement appears to be dose-dependent and occurs at the same time as cardiovascular changes. Later, there may be other changes compatible with adult respiratory distress syndrome (ARDS). Swelling of the lung can be a result of heart failure, ARDS, or aspiration of stomach contents. Symptoms related to acidosis such as fast or excessive breathing are frequently observed; however, major symptoms such as swelling of the lung and inflammation of the bronchi and lungs are relatively rare, and are usually seen only in extreme poisoning.</p> <p>Cardiovascular effects: Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of ethylene glycol poisoning by swallowing, which is 12-24 hours after acute exposure. The symptoms of poisoning involving the heart include increased heart rate, heart enlargement and ventricular gallop. There may also be high or low blood pressure, which may progress to cardiogenic shock. In lethal cases, inflammation of the heart muscle has been observed at autopsy. Cardiovascular involvement appears to be rare and usually seen after swallowing higher doses of ethylene glycol. In summary, acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.</p> <p>Gastrointestinal effects: Common early acute effects of swallowing ethylene glycol include nausea, vomiting with or without blood, heartburn and abdominal cramping and pain. One patient showed intermittent diarrhea and pain, and after surgery, deposition of oxalate crystals was</p>

Continued...



## DefendAL HD ELC Coolant Concentrate /RTU

shown to have occurred.

Musculoskeletal effects: Reported musculoskeletal effects in cases of acute ethylene glycol poisoning include diffuse muscle tenderness and pain, associated with high levels of creatinine in the blood, and jerks and contractions associated with low calcium.

Liver effects: Autopsies carried out on people who died following acute ethylene glycol poisoning showed deposition of calcium oxalate in the liver as well as hydropic and fatty degeneration and cell death (necrosis) of the liver.

Kidney effects: Adverse kidney effects are seen during the third stage of ethylene glycol poisoning, 2-3 days after acute exposure. Calcium oxalate crystals are deposited in the tubules and are seen in the urine. There may also be degeneration and death of tubule cells, and inflammation of the tubule interstitium. If untreated, the degree of kidney damage progresses and leads to blood and protein in the urine, decreased kidney function, reduction in urine output and ultimately, kidney failure. With adequate supportive therapy, kidney function can return to normal or near normal.

Metabolic effects: Metabolic changes can occur within 12 hours of exposure to ethylene glycol. There may be metabolic acidosis, caused by accumulation of glycolic acid in the blood and therefore a reduction in blood pH. The anion gap is increased, due to increased unmeasured anions (mainly glycolate).

Effects on the nervous system: Adverse reactions involving the nervous system are among the first symptoms to appear in humans after ethylene glycol is swallowed. These early effects are also the only symptoms caused by unmetabolised ethylene glycol. Together with metabolic effects (see above), they occur from 0.5-12 hours after exposure and are considered to be part of the first stage in ethylene glycol poisoning. Inco-ordination, slurred speech, confusion and sleepiness are common in the early stages, as are irritation, restlessness and disorientation. Later, there may be effects on cranial nerves (which may be reversible over many months). Swelling of the brain (cerebrum) and crystal deposits of calcium oxalate in the walls of the small blood vessels of the brain were found at autopsy in people who died after acute ethylene glycol poisoning.

Reproductive effects: Animal testing showed that ethylene glycol may affect fertility, survival of fetuses and the male reproductive organs.

Effects on development: Animal studies indicate that birth defects may occur after exposure in pregnancy; there may also be reduction in foetal weight.

Cancer: No studies are known regarding cancer effects in humans or animal, after skin exposure to ethylene glycol.

Genetic toxicity: No human studies available, but animal testing results are consistently negative.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

DefendAL HD ELC Coolant Concentrate	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
sodium laurate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	>10mg/l	4
potassium hydroxide	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	80mg/l	2
ethylene glycol	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	8050mg/l	4
Sodium Tolytriazole	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	29mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	8.58mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	55mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC10(ECx)	504h	Crustacea	0.4mg/l	2

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Continued...

## DefendAL HD ELC Coolant Concentrate /RTU

For Ethylene Glycol: Log Kow: -1.93 to -1.36; Half-life (hr) air: 24 hrs; Henry's Law Constant: 1.41 10<sup>-3</sup> or 6.08 10<sup>-3</sup> Pa.m<sup>3</sup>/mol, (depending on method of calculation); Henry's atm m<sup>3</sup>/mol: 2.3x10 atm-m/mol; Vapor Pressure: 7.9 Pa @ 20 C; BOD 5: 0.15 to 0.81, 12%; COD: 1.21 to 1.29; ThOD: 1.26; BCF: 10 to 190.

Atmospheric Fate: In the atmosphere, ethylene glycol exists mainly in the vapor phase. It is degraded by reactions with hydroxyl radicals, (estimated half-life 24-50 hours). Direct breakdown of the substance by sunlight is not expected.

Terrestrial Fate: Soil - The substance is not expected to evaporate from soil surfaces. Ethylene glycol has little or no capacity to bind to soil and will be mobile. Several strains of microorganisms capable of utilizing ethylene glycol as a carbon source have been identified. Plants - Ethylene glycol has been identified as a metabolite of the growth regulator ethylene in a number of higher plants and as naturally occurring in the edible fungus *Tricholoma matsutake*.

Aquatic Fate: Ethylene glycol is not expected to evaporate from water surfaces. The substance is not expected to be broken down by water or bind to suspended particles. The substance has been shown to be rapidly broken down by microorganisms in surface water, (to a lesser extent in salt water).

Ecotoxicity: Ethylene glycol does not concentrate in the food chain. The substance is categorized as readily biodegradable under both oxygenated and low oxygen conditions. The substance is generally of low toxicity to marine organisms; however, toxic effects have been noted in streams receiving runoff of the substance. Field studies in the vicinity of an airport have reported toxic signs consistent with ethylene glycol poisoning, fish kills, and reduced biodiversity. These effects cannot definitively be ascribed to ethylene glycol. Terrestrial organisms are much less likely to be exposed to ethylene glycol and generally show low sensitivity to the compound. The substance is expected to have low toxicity to birds.

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)

## Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 200)

## Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (KOC = 1)

## SECTION 13 Disposal considerations

## Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> </ul>
	<p>Otherwise:</p> <ul style="list-style-type: none"> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>Reduction</li> <li>Reuse</li> <li>Recycling</li> <li>Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li><b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for treatment before disposal.</li> <li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible or consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>

## SECTION 14 Transport information

## Labels Required

	
Marine Pollutant	NO

Shipping container and transport vehicle placarding and labeling may vary from the below information. Products that are regulated for transport will be packaged and marked as Dangerous Goods in Limited Quantities according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

## Land transport (DOT)

14.1. UN number or ID number	3082
14.2. UN proper shipping	Environmentally hazardous substance, liquid, n.o.s. (ethylene glycol)

Continued...

name		
14.3. Transport hazard class(es)	Class	9
	Subsidiary Hazard	Not Applicable
14.4. Packing group	III	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Hazard Label	9
	Special provisions	8, 146, 173, 335, 441, IB3, T4, TP1, TP29

For Individual Packages of Environmentally Hazardous Substances meeting the descriptions of UN 3082 that contain LESS THAN the reportable quantity (5,000 lbs) - Not Regulated

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
sodium laurate	Not Available
potassium hydroxide	Not Available
ethylene glycol	Not Available
Sodium Tolyltriazole	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
sodium laurate	Not Available
potassium hydroxide	Not Available
ethylene glycol	Not Available
Sodium Tolyltriazole	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

sodium laurate is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

potassium hydroxide is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US CWA (Clean Water Act) - List of Hazardous Substances

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Sodium Tolyltriazole is found on the following regulatory lists

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No

Continued...

## DefendAL HD ELC Coolant Concentrate /RTU


Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

## US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
potassium hydroxide	1000	454
ethylene glycol	5000	2270

## State Regulations

## US. California Proposition 65

 **WARNING:** This product can expose you to chemicals including **ethylene glycol**, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (Sodium Tolytriazole)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (sodium laurate)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (sodium laurate; Sodium Tolytriazole)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## SECTION 16 Other information

Revision Date	10/18/2023
Initial Date	05/31/2022

## CONTACT POINT

IMMEDIATELY contact the local POISON CONTROL center for your area (24 hours): Alberta 1-800-332-1414 British Columbia 1-800-567-8911 Manitoba 1-855-776-4766 New Brunswick 911 Newfoundland and Labrador 1-866-727-1110 Northwest Territories 1-800-332-1414 Nova Scotia and Prince Edward Island 1-800-565-8161, 1-800-332-1414 or 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Quebec 1-800-463-5060 Saskatchewan 1-866-454-1212 Yukon Territory 867-393-8700 United States 1-800-222-1222  
 Contactez IMMÉDIATEMENT le centre ANTIPOLISON de votre région (24 heures): Alberta 1-800-332-1414 Colombie-Britannique 1-800-567-8911 Manitoba 1-855-776-4766 Nouveau-Brunswick 911 Terre-Neuve-et-Labrador 1-866-727-1110 Territoires du Nord-Ouest 1-800-332-1414 Nouvelle-Écosse et Île-du-Prince-Édouard 1-800-565-8161, 1-800-332-1414 ou 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Québec 1-800-463-5060 Saskatchewan 1-866-454-1212 Territoire du Yukon 867-393-8700 États-Unis: 1-800-222-1222

## SDS Version Summary

Version	Date of Update	Sections Updated
---------	----------------	------------------

Continued...

## DefendAL HD ELC Coolant Concentrate /RTU

Version	Date of Update	Sections Updated
6.18	10/17/2023	Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Ecological Information - Environmental, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire incompatibility), First Aid measures - First Aid (inhaled), First Aid measures - First Aid (swallowed), Composition / information on ingredients - Ingredients, Exposure controls / personal protection - Personal Protection (Respirator), Exposure controls / personal protection - Personal Protection (hands/feet), Accidental release measures - Spills (major), Accidental release measures - Spills (minor), Handling and storage - Storage (storage incompatibility), Handling and storage - Storage (suitable container)

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average  
 PC - STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 ES: Exposure Standard  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index  
 DNEL: Derived No-Effect Level  
 PNEC: Predicted no-effect concentration  
 AIIC: Australian Inventory of Industrial Chemicals  
 DSL: Domestic Substances List  
 NDSL: Non-Domestic Substances List  
 IECSC: Inventory of Existing Chemical Substance in China  
 EINECS: European INventory of Existing Commercial chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 NLP: No-Longer Polymers  
 ENCS: Existing and New Chemical Substances Inventory  
 KECI: Korea Existing Chemicals Inventory  
 NZIoC: New Zealand Inventory of Chemicals  
 PICCS: Philippine Inventory of Chemicals and Chemical Substances  
 TSCA: Toxic Substances Control Act  
 TCSI: Taiwan Chemical Substance Inventory  
 INSQ: Inventario Nacional de Sustancias Químicas  
 NCI: National Chemical Inventory  
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.